

PRODUCT FACT SHEET



DULUX[®] DUREBILD[®] STE GF

The Surface Tolerant Glass Flake Epoxy

DULUX® DUREBILD® STE GF

Durebild® STE GF is a two-pack, high-solids surface-tolerant epoxy with glass flake for enhanced protection against corrosion and abrasion in a wide variety of heavy industrial applications. Its tenacious adhesion to most surfaces makes it an excellent universal tie-coat over existing paintwork, or as a primer/intermediate over power tool cleaned steel. The high build characteristics allow higher film builds in fewer coats, saving time and money. Durebild® STE GF comes in Mid Grey and Black.

USES

Durebild® STE GF can be used as a primer/finish on internal areas or in immersion. On external areas subject to UV, Durebild® STE GF is an excellent intermediate coat for two-pack topcoats.

FEATURES

- Surface Tolerant – tenacious adhesion
- Excellent barrier in immersion or splash zone area
- High solids and high build formulation
- Cold Cure hardener available
- Chemical resistant

BENEFITS

- Higher film builds achievable in fewer coats
- Cold Cure Hardener allows year round use
- High durability offers lower maintenance

PERFORMANCE GUIDE

Weatherability	Will chalk on UV exposure
Heat Resistance	Up to 120°C dry heat
Water Resistance	Outstanding resistance to immersion
Abrasion Resistance	Excellent
Solvent Resistance	Resists most solvents
Acid Resistance	Good
Alkali Resistance	Excellent
Salt Resistance	Excellent
Standards & Tests	AS 3750.1, Approved to APAS 2977

APPLICATION

Spray, brush and roller.

