

DULUX® DUREMAX® GPE

Duremax® GPE is a two-pack general purpose epoxy primer that can be easily applied by spray, brush and roller. This versatile product exhibits both strong adhesion and cohesion to form an extremely tough barrier to offer passive barrier protection. A Fast Cure Hardener and a Quickturn™ Hardener are also available, offering faster touch & handle times. Untinted Duremax® GPE, when used with Fast Cure Hardener, is suitable for potable water.



On internal steelwork in mild dry environments, Duremax® GPE can be used as a primer/finish. On externally exposed steelwork subject to UV, Duremax® GPE can be topcoated in any of our two pack or single pack topcoats.

FEATURES

- Full range of colours plus MIO Mid Grey
- Two-pack epoxy excellent adhesion to most substrates
- Ease of application with brush, roller or spray
- Higher builds achievable superior barrier protection
- Fast Cure and Quickturn™ hardeners available

BENEFITS

- Cold Cure Hardener allows year round use
- Quick Turn Hardener for rapid production output and minimal down time

PERFORMANCE GUIDE

Weatherability	Will chalk on UV exposure
Heat Resistance	Up to 120°C dry heat
Water Resistance	Outstanding resistance to immersion
Abrasion Resistance	Very good
Solvent Resistance	Resists most solvents
Acid Resistance	Good
Alkali Resistance	Excellent
Salt Resistance	Excellent
Standards & Tests	AS/NZ 3750.4. Approved to AS4020 (with Fast Cure Hardener)

APPLICATION

Spray, brush and roller





