

PRODUCT FACT SHEET



# DULUX<sup>®</sup> FERREKO<sup>®</sup> No. 3

The Micaceous Iron Oxide Epoxy



# DULUX® FERREKO® No. 3

Ferreko® No. 3 is a two-pack epoxy formulated with a high level of micaceous iron oxide, offering outstanding durability and abrasion resistance even in aggressive coastal and industrial environments. Ferreko® No. 3 resists UV exposure and moisture penetration with minimum chalking. This versatile product may be used as an intermediate coat under polyurethane for enhanced barrier properties, or as the intermediate and finish coat where both the barrier properties and the “industrial aesthetics” of a micaceous iron oxide are desired.

## USES

Ferreko® No. 3 is typically used for the protection of steel in aggressive environments such as wharf super-structures, ship loaders, chemical plants, bridges, infrastructure, conveyors, silos and tanks.

## FEATURES

- Suitable in the most harsh environments
- Subtle metallic lustre
- Highly resistant to UV and weathering
- Outstanding moisture resistance
- Suitable for immersion (Natural Grey only)

## BENEFITS

- Far superior corrosion protection than conventional coatings
- Equally suitable as an intermediate coat or a finish coat
- Low maintenance

## PERFORMANCE GUIDE

Weatherability	Excellent
Heat Resistance	Up to 150°C dry heat
Water Resistance	Suitable for immersion (Natural Grey)
Abrasion Resistance	Excellent
Solvent Resistance	Excellent resistance to most solvents
Acid Resistance	Good
Alkali Resistance	Excellent
Salt Resistance	Excellent
Standards & Tests	AS/NZ 3750.14

## APPLICATION

Spray

