

PRODUCT FACT SHEET

Dulux
PROTECTIVE COATINGS

DULUX[®] LUXATHANE[®] HPX

The High Performance Polyurethane



DULUX® LUXATHANE® HPX

Luxathane® HPX is a high gloss, two-pack polyurethane finish with outstanding UV resistance and gloss retention – the premium topcoat where high visual impact and long term durability are important. Specially formulated for spray application in shop, Luxathane® HPX is easy to apply to a smooth, high gloss finish. Equally suitable for both exterior and interior areas, Luxathane® HPX offers design flexibility. The good drying characteristics of Luxathane® HPX offers fast touch and handle times.

USES

Luxathane® HPX is designed for general use in industrial, chemical and marine environments where excellent gloss and colour retention during extended service periods is required. It has the versatility to be used in new construction and maintenance services over properly primed steel, galvanised steel, aluminium, concrete, hardwood timber and MDF.

FEATURES

- Full range of colours
- Excellent gloss retention – outstanding durability
- Smooth high gloss finish
- Good handling and drying properties

BENEFITS

- Ease of use, offers a quality finish
- Maintains asset value
- Reduced handling times

PERFORMANCE GUIDE

Weatherability	Excellent
Heat Resistance	Up to 120°C dry heat.
Water Resistance	Excellent. Not suitable for immersion
Abrasion Resistance	Very Good
Solvent Resistance	Resists most solvents
Acid Resistance	Good
Alkali Resistance	Good
Salt Resistance	Excellent
Standards & Tests	AS 3750.6

APPLICATION

Spray, brush and roller

