

Dulux[®]

**PROTECTIVE
COATINGS**

Product Fact Sheet

Weathermax[®] HBR

Weathermax[®] HBR is a two-pack, high-build, gloss polyurethane with high UV and chemical resistance – the perfect topcoat for a wide range of applications.

CityLink
VIC

Perth Hospital
Kid's Bridge
(Koolangka)
WA

Protection you can count on.

Weathermax® HBR

High Build Recoatable Polyurethane

Weathermax® HBR has been locally developed for high build roller or brush application. It is a high build recoatable polyurethane coating used over a wide range of suitably primed substrates such as mild steel, galvanised steel, concrete and aluminium.

APAS 2911/1 assessed and confirmed to meet all requirements on specific certified products.

Features

- Excellent brush & roller application
- Can be spray applied up to 125 microns DFT in a single coat
- Superior gloss and colour retention
- Excellent resistance to most graffiti media and cleaning agents
- Tintable – available in over 5000 colours
- Accelerator available for use in cooler conditions

Benefits

- Much higher film builds achievable in fewer coats
- Cold Cure Hardener allows year round use
- High durability offers lower maintenance

Product overview

Chemistry	Polyurethane
Product type	Topcoat
Volume solids	70% (White)
VOC level	<280 g/L
Dry film thickness (min-max)	75-125µm
Gloss retention	Excellent
Abrasion resistance	Good
Water resistance	Excellent but not suitable for immersion
Specifications	APAS 2911/1, AS 4548.5 Appendix C & D, AS 3750.6

Refer to product datasheet for more details.

T 13 23 77

T 0800 800 424

www.duluxprotectivecoatings.com.au

© Dulux and Weathermax are registered trademarks of DuluxGroup (Australia) Pty Ltd. DuluxGroup (Australia) Pty Ltd (ABN 67 000 049 427) 1956 Dandenong Road, Clayton, 3168, Australia. DuluxGroup (New Zealand) Pty Ltd (ABN 55 133 404 118) 150 Hutt Park Road, Lower Hutt, 5010 New Zealand.



Jacobs Ladder
NZ

MIT Manukau
NZ

