

## Product Fact Sheet

# Luxathane® MPX

A subtle, matt finish polyurethane that is suitable for both interior and exterior use.



**Protection you can count on.**

# Luxathane® MPX

## Contemporary, subtle matt finish

Luxathane MPX is a two-component, acrylic polyurethane matt topcoat. Ideal for steelwork and facades of commercial projects. Suitable for both internal and external conditions, this contemporary aesthetic finish provides the durability and performance that is expected from the Luxathane range.

Luxathane MPX has been designed to withstand harsh Australian and New Zealand conditions, resulting in a long lasting matt finish.

### Feature

- Smooth matt finish
- Over 5000 tintable colours available
- Good gloss retention
- Very good drying and handling properties
- Extended recoatability
- Accelerator available to reduce dry times
- Suitable for new construction and maintenance

### Product overview

Chemistry	Polyurethane
Product type	Topcoat
Volume solids	47±2% (white)
VOC level	<540 g/L (white)
Dry film thickness (min–max)	50–70µm
Gloss retention	Good
Abrasion resistance	Good
Water resistance	Excellent but not suitable for immersion

Refer to product datasheet for more details.



T 13 23 77

[www.duluxprotectivecoatings.com.au](http://www.duluxprotectivecoatings.com.au)

© Dulux and Luxathane are registered trademarks of DuluxGroup (Australia) Pty Ltd. DuluxGroup (Australia) Pty Ltd (ABN 67 000 049 427) 1956 Dandenong Road, Clayton, 3168, Australia. DuluxGroup (New Zealand) Pty Ltd (ABN 55 133 404 118) 150 Hutt Park Road, Lower Hutt, 5010 New Zealand.