

Dulux[®]

PROTECTIVE
COATINGS

Product Fact Sheet

Luxathane[®] HPX

A smooth, high gloss finish polyurethane with good UV resistance and gloss retention.



Protection you can count on.

Luxathane® HPX

Smooth, high gloss finish

Luxathane HPX is a two-component, acrylic polyurethane high-gloss topcoat that provides long term recoatability. Its high-gloss smooth finish and good abrasion resistance makes it suitable for industrial and architectural steelwork and facades.

When applied over Dulux Protective Coatings epoxy coatings, Luxathane's ability to withstand harsh weather and environmental conditions, makes it an excellent anti-corrosion system.

Feature

- Smooth high gloss finish
- Over 5000 tintable colours available
- Good gloss retention
- Very good drying and handling properties
- Extended recoatability
- Accelerator available to reduce dry times
- Suitable for new construction and maintenance

Product overview

| | |
|------------------------------|--|
| Chemistry | Polyurethane |
| Product type | Topcoat |
| Volume solids | 56% (white) |
| VOC level | <410 g/L (untinted, white) |
| Dry film thickness (min-max) | 50-75µm |
| Gloss retention | Good |
| Abrasion resistance | Good |
| Water resistance | Excellent but not suitable for immersion |

Refer to product datasheet for more details.



T 13 23 77

www.duluxprotectivecoatings.com.au

© Dulux and Luxathane are registered trademarks of DuluxGroup (Australia) Pty Ltd. DuluxGroup (Australia) Pty Ltd (ABN 67 000 049 427) 1956 Dandenong Road, Clayton, 3168, Australia. DuluxGroup (New Zealand) Pty Ltd (ABN 55 133 404 118) 150 Hutt Park Road, Lower Hutt, 5010 New Zealand.