

**Dulux**<sup>®</sup>

PROTECTIVE  
COATINGS

Product Fact Sheet

# Luxathane<sup>®</sup> SPX

A versatile, satin finish polyurethane that is suitable for industrial and commercial structures.



**Protection you can count on.**

# Luxathane® SPX

## Versatile, satin finish

Luxathane SPX is a two-component, acrylic polyurethane satin topcoat that can be used on a wide variety of applications. Its gloss retention and surface hardness makes it suitable for commercial projects such as retail complexes and high rise offices, as well as outdoor ornamental sculptures.

Formulated for use in commercial and industrial areas where extended service periods are required.

### Feature

- Smooth satin finish
- Over 5000 tintable colours available
- Good gloss retention
- Very good drying and handling properties
- Extended recoatability
- Accelerator available to reduce dry times
- Suitable for new construction and maintenance

### Product overview

Chemistry	Polyurethane
Product type	Topcoat
Volume solids	52±2% (white)
VOC level	<430 g/L (white)
Dry film thickness (min-max)	50-70µm
Gloss retention	Good
Abrasion resistance	Good
Water resistance	Excellent but not suitable for immersion

Refer to product datasheet for more details.



T 13 23 77

[www.duluxprotectivecoatings.com.au](http://www.duluxprotectivecoatings.com.au)

© Dulux and Luxathane are registered trademarks of DuluxGroup (Australia) Pty Ltd. DuluxGroup (Australia) Pty Ltd (ABN 67 000 049 427) 1956 Dandenong Road, Clayton, 3168, Australia. DuluxGroup (New Zealand) Pty Ltd (ABN 55 133 404 118) 150 Hutt Park Road, Lower Hutt, 5010 New Zealand.