



PROTECTIVE  
COATINGS

Product Fact Sheet

# Luxafloor® HSG

High Solids Gloss Epoxy For Concrete Floors



## Luxafloor® HSG

LUXAFLOOR® HSG (High Solids Gloss) is a high gloss two-pack epoxy for coating concrete floors. It is high build, making it an ideal choice for coating floors that are subject to heavy traffic.

LUXAFLOOR® HSG comes in tint-able bases and is available in a large range of colours using the Dulux COLORFAST™ tint system.

LUXAFLOOR® HSG is ideal for interior flooring applications where a high gloss finish is required. Recommended application areas include warehouses, retail areas, showrooms, and manufacturing facilities.

### Features

- Very high gloss finish
- Ideal for interior areas subject to high wear
- Easy to apply – good flow out
- Tint-able – available in a large range of colours
- Excellent chemical resistance

### Application

Brush and roller application

### Product overview

Chemistry	Epoxy
Product type	High Solids Topcoat
Volume solids	88% (white)
VOC level	<100 g/L (white, untinted)
Recommended dry film thickness (per coat)	100 µm (Spread rate of 8.8M <sup>2</sup> /L)
Abrasion resistance	Excellent when fully cured
Chemical resistance	Excellent*

\*Please see the Product Data Sheet on our website for more detailed information including a chemical resistance table



[www.duluxprotectivecoatings.com.au](http://www.duluxprotectivecoatings.com.au)

® Dulux and Luxafloor are registered trade marks of DuluxGroup (Australia) Pty Ltd. DuluxGroup (Australia) Pty Ltd (ABN 67 000 049 427) 1956 Dandenong Road, Clayton, 3168, Australia. DuluxGroup (New Zealand) Pty Ltd (ABN 55 133 404 118) 150 Hutt Park Road, Lower Hutt, 5010 New Zealand.  
© Dulux Protective Coatings GXIX.