

**Dulux**<sup>®</sup>

PROTECTIVE  
COATINGS

Product Fact Sheet

# Luxathane<sup>®</sup> HPX

A smooth, high gloss finish polyurethane with excellent UV resistance and gloss retention.



**Protection you can count on.**

# Luxathane® HPX

## Smooth, high gloss finish

Luxathane HPX is a two-component, acrylic polyurethane high-gloss topcoat that provides long term recoatability. Its high-gloss smooth finish and good abrasion resistance makes it suitable for industrial and architectural steelwork and facades.

When applied over Dulux Protective Coatings epoxy coatings, Luxathane's ability to withstand harsh weather and environmental conditions makes it an excellent anti-corrosion system.

**Feature**

- Smooth high gloss finish
- Over 5000 tintable colours available
- Excellent gloss retention
- Very good drying and handling properties
- Extended recoatability
- Accelerator available to reduce dry times
- Suitable for new construction and maintenance

**Product overview**

Chemistry	Polyurethane
Product type	Topcoat
Volume solids	56% (white)
VOC level	<410 g/L (untinted, white)
Dry film thickness (min-max)	50-70µm
Gloss retention	Excellent
Abrasion resistance	Excellent
Water resistance	Excellent but not suitable for immersion

Refer to product datasheet for more details.

T 13 23 77

T 0800 800 424

[www.duluxprotectivecoatings.com.au](http://www.duluxprotectivecoatings.com.au)

© Dulux and Luxathane are registered trademarks of DuluxGroup (Australia) Pty Ltd. DuluxGroup (Australia) Pty Ltd (ABN 67 000 049 427) 1956 Dandenong Road, Clayton, 3168, Australia. DuluxGroup (New Zealand) Pty Ltd (ABN 55 133 404 118) 150 Hutt Park Road, Lower Hutt, 5010 New Zealand.

