

Luxafloor® Colour Chart



Protection you can count on.

The Dulux® Protective Coatings Colour Chart displays the colours available across the Luxafloor® range.

A wide range of colours are available in Luxafloor LGE, Luxafloor HSG and Luxafloor PTX.

For Luxafloor WB, Luxafloor ECO2 and Luxafloor FCF, where there is a limited colour offering, please refer to the legend below.

Legend

- W** Luxafloor WB
- E** Luxafloor ECO₂
- F** Luxafloor FCF

Dulux World of Colour and AS2700 colours can be matched to our tintable Luxafloor coatings.

Always check the product data sheet or consult with your Dulux Representative before selecting colours, as some Luxafloor® products are tintable, while others are only available in the colours nominated on the product data sheet.

About Colour

All Dulux® Protective Coatings products and colours are lead-free and chromate-free. Some colours containing red and yellow pigments may have lower opacity than their lead-based and chromate-based equivalents, and therefore products containing these colours may require additional coats to achieve full opacity.

Paint may dry darker compared to a wet sample and may appear darker or lighter on larger areas.

Light source (ie incandescent, fluorescent, halogen or natural light) and brightness can also greatly influence colour perception.

Colour variations may occur across different products, due to factors, such as resin type, type of hardener used and gloss level. The higher the gloss, the darker and more saturated the perceived colour.

When using tinted products ensure all containers have been tinted to the correct colour before use. It is recommended that all containers are boxed together before use to ensure colour consistency. It is the Applicator's responsibility to check that the correct colour has been supplied. Dulux® assumes no responsibility for application of an incorrect colour.

Whilst every effort has been made to accurately match the colours represented on this colour chart with the actual product colour, there may be colour variation due to the printing process. To ensure best accuracy please confirm your colour choice by ordering a Dulux A4 colour swatch.



Luxafloor® Colour Chart

					
Ashville	Favoured	Vanessa Mae	Ghosting	Paving Stone	Koala Grey N45
					
Silver Thaw	Moxa	Pelaco	Powered Rock	Warm Granite	Rakaia
					
Missouri Mud	Excelsior	Tadpole	Oyster Linen	Barnfloor	Organic
					
Dieskau	Puppy	Easily Suede	Narrow Neck	Stony Creek	Randall
					
Limed White	Pale Earth	Light Leather	Linseed	Buffhide	Army Issue
					
Loop Hole	Time Capsule	Deep Clay	Kahlua Milk	Knapsack	Swampy
					
Moth Pink	Chicory	Lavenbrun	Balsa Stone	Malt Shake	Osso Bucco
					
Young Turk	Rosetta	Savin	Camel Cord	Germania	Hay Wain
					
Adobe	Signal Red	R13	Happy	Stella	Vivid Yellow Y13
					
Venetian Red	R62				

Luxafloor® Colour Chart



Terrace White Miller Mood Aerobus



Platinum Class Bretz Water Worn



Tranquil Retreat Endless Dusk Timeless Grey



Highgate Madigan Lightbox Grey N33



Celtic Sky Wily William Light Grey N35



Grey Pail Dialogue Blue Grey N53



Spanish Olive Gamelan Sepal



Pozieres Viridis Knave W



Coalition Goyder Green Jiping W



Cameo Blue Illusion Blue Identity E



Blue Ballerina Ice Cave Pinafore Blue



Flight Time Cottonwool Blue Bluebell W B41



Clunies E Padded Leaf Cypress Garden W



Silver Drop Rainford W Lilly Pad W



White Spruce Club Moss W Jade G21



Pre School Blue Balm Light Grey Blue E B44



Sky Bus Adventure Isle Atlantic Gull



Charter Summer Sky Harbour Blue B24

Luxafloor® is a high performance range of concrete floor coatings suitable for industrial applications such as office areas, commercial car parks & garage floors, warehouses, manufacturing facilities, retail areas and showrooms.

Luxafloor® Product Summary

	Product	Interior/ Exterior	Pot Life*	Dry Times			Volume Solids	Spreading Rate (sqm/L)	Colour Range
				Light Traffic	Recoat* ¹	Full Cure*			
Water Based	Luxafloor WB	Interior	1 Hour	24 Hours	6 Hours	7 Days	50%	7.7	Tintable
	Luxafloor ECO ₂	Interior	2 Hours	24 Hours	4 Hours	7 Days	42%	6.5	Limited
Express	Luxafloor FCF	Both	8 hours	2 Hours	2 Hours	1 Day	75% (White)	10.0	Limited
	Luxafloor Primer	Interior	1 Hour	3 Hours	3 Hours	7 Days	64%	7.2	No
High Build	Luxafloor LGE	Interior	1.5 Hours	24 hours	14 Hours	7 Days	84% (White)	6.7	Tintable
	Luxafloor HSG	Interior	1 Hour	16 hours	6 Hours	7 Days	85% (White)	7.0	Tintable
	Luxafloor PTX	Both	2 Hours	24 hours	10 Hours	7 Days	70% (White)	7.0	Tintable
Clears	Luxafloor CFS	Both	N/A	1 Hour	1 Hour	7 Days	15%	10.0	No
	Luxafloor CP	Both	N/A	24 hours	12 Hours	7 Days	43% (Gloss)	10.8	No

For further product information refer to the relevant product data sheet.

* All figures are measured at 25°C and 50% relative humidity. Figures will vary when applied outside of these parameters.

1. Light traffic refers to the suitable amount of time before the floor can be walked on. Recoat time refers to the minimum amount of time before the floor can be recoated.



Australia

T 13 23 77

New Zealand

T 0800 800 424

® Dulux, Luxafloor and Roadmaster are registered trademarks of DuluxGroup (Australia) Pty Ltd

DuluxGroup (Australia) Pty Ltd (ABN 67 000 049 427)
1956 Dandenong Road, Clayton, 3168, Australia

DuluxGroup (New Zealand) Pty Ltd (ABN 55 133 404 118)
150 Hutt Park Road, Lower Hutt, 5010 New Zealand



www.duluxprotectivecoatings.com.au

© Dulux, the Squares Device and Luxafloor are registered trade marks of DuluxGroup (Australia) Pty Ltd. © Colour names denoted with an alpha numeric designation are Standards Australia Ltd copyrighted material that is distributed by SAI Global on Standards Australia Ltd's behalf. It may be reproduced in accordance with the terms of SAI Global Ltd's Licence 1505-c008 to Color Communications Inc. Australasia Ltd. All licensed copies of this document must be obtained from the Licensee. Standards Australia Ltd's material is not for resale, reproduction or distribution in whole or part without written permission from SAI Global Ltd: Tel +61 2 8206 6355 or copyright@saiglobal.com